

Visqueen Flame Retardant Polythene Protection

Features and benefits

- Manufactured in the UK by Visqueen
- LPS1207 cert.no 1792a - 3rd party flame retardant certification
- Large roll format - Ideal for draping, screening, covering or hanging. Quick and easy installation.
- Flame retardant - helps reduce the risk of losses from fires on construction sites
- LPS1207 temporary protection - helps avoid delay penalties to fast-track build programmes when areas are exposed to damage
- LPS1207 cert.no 1792a - Complies with the Joint Code of Practice Insurance requirements
- 0.25mm (1000 gauge) thick - Approved for asbestos removal or wrapping film
- Multi-use - can be cut and fitted for pallet hood cover & door protection

Product description

Visqueen Flame Retardant Polythene Protection is manufactured using virgin polymers with specialty additives to ensure the product is flame retardant to LPS1207 - Loss Prevention Standard cert no. 1792a. It is supplied on a core in rolls of:

4m x 25m x 250 micron (1000 gauge) Orange - Certificate 1792a/02 applies

4m x 50m x 65 micron (260 gauge) White - Certificate 1792a/01 applies

Other sizes are available on request, subject to minimum order quantities.

The LPS1207 certification covers thicknesses between 50 and 250 micron, in white or orange.

Approvals and standards

- LPCB: LPS1207 Loss Prevention Standard certificate no. 1792a
- Ignitability (Small & Large tests) (BS 476: Part 12:1991 & LPS: BS5852)
- Smoke Emissions Test (prEN 2825 & prEN 2824)
- Toxic Gas Emission Test (prEN 2826 & prEN 2824)
- Critical Oxygen Index (BS 2782: Part 1: Method 141: 1986)
- Quality Management System ISO 9001:2015

Usage

The LPS1207 Visqueen Flame Retardant Polythene Protection can be used for screening off individual areas, draping and for a variety of surfaces. Suitable for wrapping large pieces of asbestos or asbestos tent and enclosure applications. The product can be easily cut and re-sized for pallet hood / cover protection. Please note the product is not approved for shrinking (heat) which will invalidate the certification if done so.

It can be also used in various other applications whilst buildings undergo refurbishment work or in new build construction projects whilst also providing protection from dust and the risks of electrical hazards.


The LPS1207 certification ensures compliance when insurers, developers and owners have a clause in the main contractors policy requesting compliance with "LPS1207" and 'The Joint Code of Practice'. Using flame retardant materials helps reduce the risk of losses from fires on construction sites.

Fast track build programmes and delay penalties now see internal finishes installed at an earlier stage within the build programme. This means finishes are exposed to following trades leaving the potential for damage. Any repair or cleaning can prove costly and time consuming and can result in a delay in hand over of the premises. The product allows for finishes to be installed, then protected, meaning the site can progress as planned.

System components

- VisqueenPro Single Sided Tape, 75mm x 25m

Find your local stockist



Visqueen Flame Retardant Polythene Protection

Storage and handling

Store in a warm, dry and clean environment in its current packaging, away from sunlight. The rolls should be stored horizontally, under cover in its original packaging.

Care should be taken when handling the product in line with current manual handling regulations.

The product is intended for indoor use only as per the the LPS1207 certificate.

Preparation

Surfaces must be smooth and free from sharp protrusions.

Installation

Material should be laid print (LPS logo) uppermost. Unroll the material and cut to fit the area to which is going to be protected.

When jointing allow an overlap gap of at least 75mm to provide a trip or dust free joint and tape securely with a single sided tape.

Smooth down all taped joints and perimeters by applying pressure along their length.

Usable temperature range

It is recommended that the polythene film is used between 5oC and 50oC. Softening point is typically >70oC.

Additional information

Using Flame Retardant Products will significantly diminish fire loading. Furthermore, the use of LPS 1207 approved products is an assurance that ample and reasonable steps have been taken to reduce the risk of fire. All products have the relevant accreditation body approval mark and manufacturers certificate number.

Visqueen Flame Retardant Polythene Protection

Property	Thickness	Dimensions
Visqueen 250 micron stock item	0.25mm (1000 gauge)	4m x 25m
Visqueen 65 micron stock item	0.065mm (260 gauge)	4m x 50m
LPS1207 test property	Method	Result
Ignitability	BS 476 part 12	pass
Smoke emissions	prEN 2824 and 5	pass
Toxic gas	prEN 2824 and 6	pass
Critical oxygen index	BS 2782 part 1	pass

Health and safety information

Refer to Visqueen safety datasheet (SDS)

Visqueen Flame Retardant Polythene Protection

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural
Waterproofing



Gas
Protection



Damp Proof
Membrane



Tapes



Damp Proof
Course



Stormwater



Vapour
Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.