

## Declaration of Performance

Unique identification code of the product-type:

| 1. | Product name                    | Colour | Thickness  |
|----|---------------------------------|--------|------------|
|    | Visqueen RadonBlok 400 Membrane | Purple | 400 micron |

| 2. | Intended use   | for damp proofing in buildings                                |
|----|--|---|
| 3. | Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)            | Visqueen<br>Maerdy Industrial Estate<br>Rhydney, UK, NP22 5PY |
| 4. | Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):        | Not relevant  |
| 5. | System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V | System 2+   |
| 6. | a. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard            | EN 13967:2012   |
|    | Notified body/ies  | Eurofins 0809   |
| 6  | b. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued    | Not relevant  |

### 7. Declaration performance

| 7 | Essential Characteristics       | Method          | Performance              | Harmonised Technical Specification |
|---|---------------------------------|-----------------|--------------------------|------------------------------------|
|   | Reaction to Fire                | EN13501-1       | F                        | EN 13967:2012                      |
|   | Watertightness                  | EN 1928 (A)     | Pass                     |                                    |
|   | Resistance to Impact            | EN 12691(A)     | 300mm                    |                                    |
|   | Resistance to static loading    | EN 12730        | 15Kg                     |                                    |
|   | Resistance to tearing (nail) MD | EN 12310-1      | 225N                     |                                    |
|   | Resistance to tearing (nail) CD | EN 12310-1      | 230N                     |                                    |
|   | Durability against heat ageing  | EN 13967 & 1928 | Pass                     |                                    |
|   | Durability against chemicals    | EN 13967 & 1928 | Pass                     |                                    |
|   | Water vapour resistance         | EN 1931 (B)     | 1193 MNs/g               |                                    |
|   | Water vapour permeability       | EN 1931 (B)     | 0.12 g/m <sup>2</sup> /d |                                    |
|   | Tensile properties MD           | EN 12311 (B)    | 22.5 MPa                 |                                    |
|   | Tensile properties CD           | EN 12311 (B)    | 20.9 MPa                 |                                    |
|   | Tensile break elongation MD     | EN 12311 (B)    | 416.5%                   |                                    |
|   | Tensile break elongation CD     | EN 12311 (B)    | 447.1%                   |                                    |
|   | Shear of Joints                 | EN 12317-2      | 224N/50mm                |                                    |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Place

Signature

Date

Derbyshire, UK



15/02/2022

Cameron Yates  
 Technical Product Manager