

Declaration of Performance

Unique identification code of the product-type:

1.	Product name	Colour	Thickness
	Visqueen Gas Resistant Self Adhesive Membrane	Black	1.2mm

2.	Intended use	for damp proofing in buildings, including basement tanking
3.	Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)	Visqueen Heanor Gate Industrial Estate, Derbyshire, DE75 7RG
4.	Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):	Not relevant
5.	System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V	System 2+
6.	a. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard	EN 13969:2004
	Notified body/ies	0836, 0809
6	b. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued	Not relevant

7. Declaration performance

7	Essential Characteristics	Performance	Harmonised Technical Specification
	Reaction to Fire	E	EN 13969:2004
	Water tightness	Pass	
	Resistance to Impact	≥500mm	
	Resistance to static loading	20Kg	
	Water tightness after ageing	Pass	

To view all test results, refer to Visqueen Gas Resistant Self Adhesive Membrane datasheet

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Place

Signature

Date

Derbyshire, UK



17/12/2020

Cameron Yates
Technical Product Manager