



Declaration of Performance

Unique identification code of the product-type:

1.	Product name	Colour	Thickness
	Visqueen Vapour Barrier	Green	300 micron

2.	Intended use	for water vapour control layers in buildings
3.	Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)	Visqueen Heanor Gate Industrial Estate, Derbyshire, DE75 7RG
4.	Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):	Not relevant
5.	System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V	System 3
6.	a. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard	EN 13984:2013
	Notified body/ies	KIWA Netherlands 1640
6	b. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued	Not relevant

7. Declaration performance

7	Essential Characteristics	Performance	Harmonised Technical Specification
	Reaction to Fire	E	EN 13984:2013
	Resistance to Impact	≥250mm	
	Durability:		
	Against ageing	Pass	
	Against alkali	Pass	

To view all test results, refer to Visqueen Vapour Barrier datasheet

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Place

Signature

Date

Derbyshire, UK

13/02/2025

Cameron Yates
Technical Product Manager