

Declaration of Performance

Unique identification code of the product-type:

1.	Product name	Colour	Thickness
	Visqueen Class B FR Vapour Check	Orange	125 micron

2.	Intended use	for water vapour control layers in buildings Type A
3.	Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)	Visqueen Heanor Gate Industrial Estate, Derbyshire, DE75 7RG
4.	Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):	Not relevant
5.	System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V	System 1
6.	a. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard	EN 13984:2013
	Notified body/ies	British Board of Agrément 0836
6	b. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued	Not relevant

7. Declaration performance

7	Essential Characteristics	Performance	Harmonised Technical Specification
	Reaction to Fire	B-s1, d0	EN 13984:2013
	Resistance to Impact	≥200mm	
	Water tightness 2kPa	Pass	
	Water tightness after ageing	Pass	
	Resistance to Impact	>200mm	
	Tensile strength TD	>15 N/mm ²	
	Tensile strength CD	>15 N/mm ²	
	Elongation TD	>400%	
	Elongation CD	>400%	
	Water Vapour Transmission aged	0.481 g/m ² .d	
	Water Vapour Resistance aged	545806 (u)	
	Water Vapour Resistance aged	341	
	Water Vapour Diffusion Sd	71.6	
	Joint Strength	50N	

To view all test results, refer to Visqueen Class B FR Vapour Check datasheet

Signed for and on behalf of the manufacturer by:

Place

Signature

Date

DoP N°: VBP/CPR/VCL006
Edition: November 2022
Issue 01

UK
CA

VISQUEEN

Derbyshire, UK



Cameron Yates
Technical Product Manager

09/11/2022