Technical Datasheet

VisqueenPro Double Sided Jointing Tape, 50mm x 10m

Features & benefits

- Part of a Visqueen's DPM and gas protection BBA approved jointing system
- Provides resistance to harmful bulk gases ingress and moisture ingress

Product description

VisqueenPro Double Sided Jointing Tape is a blue, double sided butyl based self adhesive lap bonding tape with an oversize quick release film. It is available in roll format 50mm x 10m.

Approvals and standards

- Visqueen certified with Quality Management System ISO 9001:2015
- Visqueen certified with Occupational Health and Safety System ISO 45001:2018
- Visqueen certified with Environmental Management System ISO 14001:2015

Usage

VisqueenPro Double Sided Jointing Tape is used to bond membranes (gas or damp) together along the lap joints.

To complete the joint, seal with the appropriate Visqueen single sided tape.

System components

- Visqueen Top Hat Units

Storage and handling

Store in a dry and clean environment in its current packaging. The tape should not be exposed to long periods of ultraviolet light.

In cold weather conditions (ambient temperatures below 5°C), it is recommended that the product is stored in a warm location prior to use.

For ease of installation during hot weather conditions (ambient temperatures above 25°C), it is recommended that the product is stored in a cool location prior to use. Elevated product temperatures may temporarily increase the adhesion between the siliconised release film and the adhesive, making the release film more difficult to remove. Allowing the product to cool before installation will minimise this effect.

The tape can be cut with a sharp retractable safety knife or robust scissors.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

Ensure all lap joint surfaces are clean, dry and free from contamination such as dust or sand. Ensure the surface and working area is not water logged. Avoid areas of unsupported jointing.

Installation

Apply VisqueenPro Double Sided Jointing Tape to the lap area of the laid sheet starting approximately 50mm from the membrane edge. Apply pressure to the tape to ensure the tape has adhered to the membrane. Remove release paper from the tape and overlap the adjoining membrane by minimum 150mm. For Visqueen damp proof membranes and gas protection membranes lap joints should then be sealed using the appropriate Visqueen lap tape. Once the tape is applied, the completed lap should be well rolled with firm pressure to ensure a completely sealed joint has occurred, and continuity with the adjacent sheet has been achieved.

Usable temperature range

In cold weather conditions (ambient temperatures below 5°C), it is recommended that the product is stored in a warm location prior to use.

For ease of installation during hot weather conditions (ambient temperatures above 25°C), it is recommended that the product is stored in a cool location prior to use. Elevated product temperatures may temporarily increase the adhesion between the siliconised release film and the adhesive, making the release film more difficult to remove. Allowing the product to cool before installation will minimise this effect.

Additional information

The information in this datasheet was correct at the time of publication. It is the user’s responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest

Heanor Gate Road, Heanor, Derbyshire, DE75 7RG
+44 (0) 333 202 6800 I enquiries@visqueen.com I www.visqueen.com

VisqueenPro Double Sided Jointing Tape, 50mm x 10m

datasheet supersedes all previously published editions.

Property	Result
Width	50mm
Length	10m
Colour	Blue
Adhesive type	Butyl
Dynamic Shear Adhesion	14 N/cm²
Dynamic Tensile Adhesion	18 N/cm²
180° Peel Adhesion	11 N/cm²
Moisture Vapour Transmission Rate	0.24 g/m²/d
Service Temperature Range	-40 to 90°C
Application temperature	>5°C

Health and safety information

Refer to VisqueenPro Double Sided Jointing Tape safety datasheet (SDS).

About Visqueen

Visqueen is a leading provider of construction membrane technologies and design-based solutions for ground gas, structural waterproofing, damp proofing and fire protection.

We offer complete support at every stage of the specification, including the supply chain process. As the UK's principal technical authority, we are best placed to ensure that the principal designer and contractor specify the most technically suited, durable, and competitive solution to guarantee their project is protected for the lifetime of the building.

Visqueen is at the forefront of advanced membrane technology and innovation in the construction industry, earning the trust and loyalty of specifiers throughout the UK and Europe.

For more information, visit visqueen.com or contact our sales office at +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Passive Fire Protection | Gas Protection | Damp Proof Membrane | Air and Vapor Control | Stormwater | Damp Proof Course | Temporary Protection

Visqueen Technical Support

Visqueen offer a comprehensive full nationwide technical support. Our team of CSSW qualified technical support managers provide on site design-based solutions for specifiers, contractors and builders merchants, and will ensure that from design stage to installation the project is fully risk assessed and the specification is approved by all stakeholders.

Our Technical Office, can design, prepare and manage CAD detailing, together with assisting in quantity take offs, while offering advice on technical installations and product selection.

Competency & Design

Visqueen promotes competency in building design by ensuring that its technical team possesses the necessary skills, knowledge, experience, and ethical practices. The company adopts the "golden thread of information," ensuring all project data is digitally secure and accessible throughout a building's lifecycle. This approach aligns with the Building Safety Act and aims to foster accountability and compliance with evolving regulations, providing clients with confidence in the safety and reliability of their projects.

Heanor Gate Road, Heanor, Derbyshire, DE75 7RG
+44 (0) 333 202 6800 I enquiries@visqueen.com I www.visqueen.com

VisqueenPro Double Sided Jointing Tape, 50mm x 10m

Visqueen CPD Seminars

Visqueen's CPD Seminars offer insights into Building Regulations, Standards, and industry guidance related to damp proofing, hazardous ground gas protection, and structural waterproofing. These one-hour seminars are tailored for construction design professionals and delivered by our Technical Support Managers. Visit our website to book a free CPD.

Visqueen Contract Design Services

Visqueen Contract Design Services offers a bespoke design service led by our team of Certified Surveyors in Structural Waterproofing (CSSW), providing experienced and specialised waterproofing design expertise for complex projects. We provide comprehensive support throughout the entire project, ensuring that all work meets the requirements of warranty providers and adheres to the highest standards of quality, reliability and current legislation.

Visqueen Training Academy

Based at our Derbyshire facility, the Visqueen Training Academy offers a variety of training programs across the UK. These include one-day product awareness sessions for distributors and builders' merchants, and intensive two-day courses for hands-on product installation training. Contact us for more information.

Heanor Gate Road, Heanor, Derbyshire, DE75 7RG
+44 (0) 333 202 6800 I enquiries@visqueen.com I www.visqueen.com