

VisqueenPro Vapour Edge Tape, 150mm x 15m

Features & benefits

- Part of the Visqueen air and vapour control layer (AVCL) range

Product description

VisqueenPro Vapour Edge Tape is a single sided aluminium flashing tape coated with an acrylic adhesive and a removable release film protecting the adhesive coating.

The product is available in roll format 150mm x 15m.

Approvals and standards

- Visqueen certified with Quality Management System ISO 9001:2015
- Visqueen certified with Occupational Health and Safety System ISO 45001:2018
- Visqueen certified with Environmental Management System ISO 14001:2015

Usage

VisqueenPro Vapour Edge Tape is used for gap bridging or as a flashing to seal the Visqueen air and vapour control layer at the perimeter of the installation onto substrates such as concrete, timber, plastic and steel.

Storage and handling

Store in warm, dry and clean environment in its original packaging. The flashing tape should not be exposed to long periods of ultraviolet light.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

The lap area of the Visqueen air and vapour control layer and the adjacent abutting substrate should be clean, dry and free from contamination such as dust.

The flashing tape can be cut with a sharp retractable safety knife.

Installation

When using VisqueenPro Vapour Edge Tape apply equidistant over the junction to be sealed. Apply pressure to the jointed area to ensure adhesion. Once the flashing tape is applied, the completed lap should be well rolled with firm pressure to ensure a completely sealed junction has been formed and continuity with the adjacent substrate has been achieved.

To aid formation, where possible jointed areas should be made over a solid substrate.

Usable temperature range

It is recommended that VisqueenPro Vapour Edge Tape should be installed above 5°C.

Additional information

Care should be taken to prevent the AVCL from becoming punctured, stretched or displaced when installing plasterboard or other construction board over the installed AVCL.

For additional detailing information, contact Visqueen Technical Services +44 (0) 333 202 6800.

The information in this datasheet was correct at the time of publication. It is the user's responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.

Property	Value
Roll dimensions	150mm x 15m
Application temperature range	5°C to 40°C

VisqueenPro Vapour Edge Tape, 150mm x 15m

Health and safety information

Refer to the VisqueenPro Vapour Edge Tape safety datasheet (SDS).

About Visqueen

Visqueen is a leading provider of construction membrane technologies and design-based solutions for ground gas, structural waterproofing, damp proofing and fire protection.

We offer complete support at every stage of the specification, including the supply chain process. As the UK's principal technical authority, we are best placed to ensure that the principal designer and contractor specify the most technically suited, durable, and competitive solution to guarantee their project is protected for the lifetime of the building.

Visqueen is at the forefront of advanced membrane technology and innovation in the construction industry, earning the trust and loyalty of specifiers throughout the UK and Europe.

For more information, visit visqueen.com or contact our sales office at [+44 \(0\) 333 202 6800](tel:+44(0)3332026800) or enquiries@visqueen.com

Complete Range, Complete Solution



Passive Fire Protection



Gas Protection



Damp Proof Membrane



Air and Vapor Control



Stormwater



Damp Proof Course



Temporary Protection

Visqueen Technical Support

Visqueen offer a comprehensive full nationwide technical support. Our team of CSSW qualified technical support managers provide on site design-based solutions for specifiers, contractors and builders merchants, and will ensure that from design stage to installation the project is fully risk assessed and the specification is approved by all stakeholders.

Our Technical Office, can design, prepare and manage CAD detailing, together with assisting in quantity take offs, while offering advice on technical installations and product selection.

Competency & Design

Visqueen promotes competency in building design by ensuring that its technical team possesses the necessary skills, knowledge, experience, and ethical practices. The company adopts the "golden thread of information," ensuring all project data is digitally secure and accessible throughout a building's lifecycle. This approach aligns with the Building Safety Act and aims to foster accountability and compliance with evolving regulations, providing clients with confidence in the safety and reliability of their projects.

Visqueen CPD Seminars

Visqueen's CPD Seminars offer insights into Building Regulations, Standards, and industry guidance related to damp proofing, hazardous ground gas protection, and structural waterproofing. These one-hour seminars are tailored for construction design professionals and delivered by our Technical Support Managers. Visit our website to book a free CPD.

Visqueen Contract Design Services

Visqueen Contract Design Services offers a bespoke design service led by our team of Certified Surveyors in Structural Waterproofing (CSSW), providing experienced and specialised waterproofing design expertise for complex projects. We provide comprehensive support throughout the entire project, ensuring that all work meets the requirements of warranty providers and adheres to the highest standards of quality, reliability and current



VisqueenPro Vapour Edge Tape, 150mm x 15m

legislation.

Visqueen Training Academy

Based at our Derbyshire facility, the Visqueen Training Academy offers a variety of training programs across the UK. These include one-day product awareness sessions for distributors and builders' merchants, and intensive two-day courses for hands-on product installation training. Contact us for more information.
