

## Visqueen Flame Retardant Polythene Protection

### Features & benefits

- LPS1207 certificate no. 1792a - 3rd party flame retardant certification
- Large roll format - ideal for draping, screening, covering or hanging
- Flame retardant - reduces the risk of losses from fires on construction sites
- LPS1207 certificate no. 1792a - complies with The Joint Code of Practice requirements
- 250 micron (1000 gauge) thick - approved for use as an asbestos wrapping film

### Product description

Visqueen Flame Retardant Polythene Protection is manufactured using virgin polymers with specialty additives to ensure the product is flame retardant to LPS1207 - Loss Prevention Standard certificate no. 1792a. It is supplied on a core in rolls of:

4m x 25m x 250 micron (1000 gauge) Orange - Certificate 1792a/02 applies  
 4m x 50m x 65 micron (260 gauge) White - Certificate 1792a/01 applies

Other sizes are available on request, subject to minimum order quantities.

The LPS1207 certification covers thicknesses between 50 and 250 micron, in white or orange.

### Approvals and standards

- LPCB certified - LPS1207 Loss Prevention Standard certificate no. 1792a
- Ignitability tested (Small & Large tests) (BS 476: Part 12:1991 & LPS: BS5852)
- Smoke Emissions tested (prEN 2825 & prEN 2824)
- Toxic Gas Emission tested (prEN 2826 & prEN 2824)
- Critical Oxygen Index tested (BS 2782: Part 1: Method 141: 1986)
- Visqueen certified with Quality Management System ISO 9001:2015
- Visqueen certified with Occupational Health and Safety System ISO 45001:2018
- Visqueen certified with Environmental Management System ISO 14001:2015

### Usage

The LPS1207 Visqueen Flame Retardant Polythene Protection can be used for screening off individual areas, draping, hanging and covering surfaces. Suitable for wrapping large pieces of asbestos or as asbestos tent and enclosure applications. The product can be easily cut and re-sized for pallet hood / cover protection. Please note the product is not approved for shrinking (heat) which will invalidate the certification if done so.

It can be also used in various other applications whilst buildings undergo refurbishment work or in new build construction projects whilst also providing protection from airborne dust, debris and the risks of electrical hazards.

The LPS1207 certification ensures compliance when insurers, developers and owners have a clause in the main contractors policy requesting compliance with "LPS1207" and 'The Joint Code of Practice'. Using flame retardant materials helps reduce the risk of losses from fires on construction sites.

Fast track build programmes and delay penalties now see internal finishes installed at an earlier stage within the build programme. This means finishes are exposed to following trades leaving the potential for damage. Any repair or cleaning can prove costly and time consuming and can result in a delay in hand over of the premises. The product allows for finishes to be installed, then protected, meaning the site can progress as planned.

### System components

- Visqueen FR Double Sided Vapour Tape, 20mm x 50m

### Storage and handling

Store in a warm, dry and clean environment in its current packaging, away from sunlight. The rolls should be stored horizontally, under cover in its original packaging.

Care should be taken when handling the product in line with current manual handling regulations.

The product is intended for indoor use only as per the the LPS1207 certificate.

### Preparation

Surfaces must be smooth and free from sharp protrusions.

### Installation

The product is intended for indoor use only as per the the LPS1207 certificate.

Material should be laid print (LPS logo) uppermost. Unroll the material and cut to fit the area to which is going to be

## Visqueen Flame Retardant Polythene Protection

protected. When jointing, allow an overlap of at least 75mm and tape securely with a single sided tape. Smooth down all taped joints by applying pressure along their length.

### Usable temperature range

It is recommended that the polythene film is used between 5°C and 50°C. Softening point is typically >70°C.

### Additional information

Using flame retardant products will significantly diminish fire loading. Furthermore, the use of LPS 1207 approved products is an assurance that ample and reasonable steps have been taken to reduce the risk of fire. All products have the relevant accreditation body approval mark and manufacturers certificate number.

The information in this datasheet was correct at the time of publication. It is the user’s responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.

Property	Thickness	Dimensions
Visqueen 250 micron stock item	0.25mm (1000 gauge)	4m x 25m
Visqueen 65 micron stock item	0.065mm (260 gauge)	4m x 50m
LPS1207 test property	Method	Result
Ignitability	BS 476 part 12	pass
Smoke emissions	prEN 2824 and 5	pass
Toxic gas	prEN 2824 and 6	pass
Critical oxygen index	BS 2782 part 1	pass

### Health and safety information

Refer to Visqueen Flame Retardant Polythene Protection safety datasheet (SDS)

### About Visqueen

Visqueen is a leading provider of construction membrane technologies and design-based solutions for ground gas, structural waterproofing, damp proofing and fire protection.

We offer complete support at every stage of the specification, including the supply chain process. As the UK’s principal technical authority, we are best placed to ensure that the principal designer and contractor specify the most technically suited, durable, and competitive solution to guarantee their project is protected for the lifetime of the building.

Visqueen is at the forefront of advanced membrane technology and innovation in the construction industry, earning the trust and loyalty of specifiers throughout the UK and Europe.

For more information, visit [visqueen.com](http://visqueen.com) or contact our sales office at +44 (0) 333 202 6800 or

## Visqueen Flame Retardant Polythene Protection

[enquiries@visqueen.com](mailto:enquiries@visqueen.com)


### Complete Range, Complete Solution



Passive Fire Protection



Gas Protection




Damp Proof Membrane



Air and Vapour Control



Stormwater



Damp Proof Course



Temporary Protection

### Visqueen Technical Support

Visqueen offer a comprehensive full nationwide technical support. Our team of CSSW qualified technical support managers provide on site design-based solutions for specifiers, contractors and builders merchants, and will ensure that from design stage to installation the project is fully risk assessed and the specification is approved by all stakeholders.

Our Technical Office, can design, prepare and manage CAD detailing, together with assisting in quantity take offs, while offering advice on technical installations and product selection.

### Competency & Design

Visqueen promotes competency in building design by ensuring that its technical team possesses the necessary skills, knowledge, experience, and ethical practices. The company adopts the "golden thread of information," ensuring all project data is digitally secure and accessible throughout a building's lifecycle. This approach aligns with the Building Safety Act and aims to foster accountability and compliance with evolving regulations, providing clients with confidence in the safety and reliability of their projects.

### Visqueen CPD Seminars

Visqueen's CPD Seminars offer insights into Building Regulations, Standards, and industry guidance related to damp proofing, hazardous ground gas protection, and structural waterproofing. These one-hour seminars are tailored for construction design professionals and delivered by our Technical Support Managers. Visit our website to book a free CPD.

### Visqueen Contract Design Services

Visqueen Contract Design Services offers a bespoke design service led by our team of Certified Surveyors in Structural Waterproofing (CSSW), providing experienced and specialised waterproofing design expertise for complex projects. We provide comprehensive support throughout the entire project, ensuring that all work meets the requirements of warranty providers and adheres to the highest standards of quality, reliability and current legislation.

### Visqueen Training Academy

Based at our Derbyshire facility, the Visqueen Training Academy offers a variety of training programs across the UK. These include one-day product awareness sessions for distributors and builders' merchants, and intensive two-day courses for hands-on product installation training. Contact us for more information.