Visqueen NF-Detailing Strip, 300mm x 10, 500mm x 10m

Features & benefits

- BDA Agrement Certified detailing material third party accreditation
- Flexible can be cut and shaped to various applications
- Multi-use suitable for complicated junctions, stanchions, patchwork and terminations
- Gas resistant non foil carrier membrane

Product description

Visqueen NF-Detailing Strip is a single sided strip, consisting of a white coloured polymer carrier film coated with a grey coloured cold weather butyl adhesive compound protected with a release film. It is available in roll format, 300mm x 10m and 500mm x 10m.

Approvals and standards

- BDA Agrement Certified detailing material third party accreditation
- Complies with the methane gas transmission rate, mass per unit area and thickness requirements of BS 8485:2015 + A1:2019 -
- industry standard for methane and carbon dioxide protection
- Suitable for all Characteristic Gas Situation (CS) ground gas regimes
- Conforms to the specification requirements of NHBC Amber 1 and Amber 2 applications
- Conforms to the specification requirements of BR 211:2023
- Visqueen certified with Quality Management System ISO 9001:2015
- Visqueen certified with Occupational Health and Safety System ISO 45001:2018
- Visqueen certified with Environmental Management System ISO 14001:2015

Usage

Visqueen NF-Detailing Strip is used for sealing junctions and complicated detailing in Visqueen gas protection systems, waterproofing systems, and damp proofing systems. It can be used on concrete, blockwork, brickwork, particle boards, steel work, steel stanchions and wooden substrates for both vertical and horizontal application.

Storage and handling

Store in dry and clean environment in its current packaging. The product should not be exposed to long periods of ultraviolet light.

Care should be taken when handling the product in line with current manual handling regulations.

For ease of installation, during hot weather conditions (>25°C), it is recommended to store the product in a cool location prior to use.

Preparation

Surfaces must be smooth and free from sharp protrusions, ensure the surface and working area is not water logged and is frost free. When applying to blockwork or brickwork the joints must be flush pointed. Prior to bonding, substrates such as masonry, concrete and steel should be primed using Visqueen HP Tanking Primer and allowed to dry thoroughly. Visqueen HP Tanking Primer must not be used on Insulation or ICF systems.

Visqueen NF-Detailing Strip can be cut with a sharp retractable safety knife.

Hand rollers are required during application. Typical hand rollers include 40mm silicone pressure roller and 6mm brass penny pressure roller.

Installation

Position and peel back the Visqueen NF-Detailing Strip release film and apply the pressure sensitive, self adhesive grey face to the prepared substrate. Apply pressure by rollering to ensure a full bond is achieved. All lap joints should be a minimum of 150mm and must be pressed and rolled to ensure damp, gas or waterproofing continuity.

When used for sealing membranes punctures, Visqueen NF-Detailing Strip should be lapped at least 150mm beyond the extents of the puncture.

Usable temperature range

It is recommended that Visqueen NF-Detailing Strip should be installed above -5°C. Prior to installation, ensure that frost or ice is not present on the substrate.

For ease of installation, during hot weather conditions (>25°C), it is recommended to store the product in a cool location prior to use.

Visqueen NF-Detailing Strip, 300mm x 10, 500mm x 10m

Additional information

The information in this datasheet was correct at the time of publication. It is the user's responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.

Property	Value
Widths	300mm and 500mm
Length	10m
Application temperature range	-5°C to 40°C

Health and safety information

Refer to the Visqueen-NF Detailing Strip safety datasheet (SDS)

About Visqueen

Visqueen is a leading provider of construction membrane technologies and design-based solutions for ground gas, structural waterproofing, damp proofing and fire protection.

We offer complete support at every stage of the specification, including the supply chain process. As the UK's principal technical authority, we are best placed to ensure that the principal designer and contractor specify the most technically suited, durable, and competitive solution to guarantee their project is protected for the lifetime of the building.

Visqueen is at the forefront of advanced membrane technology and innovation in the construction industry, earning the trust and loyalty of specifiers throughout the UK and Europe.

For more information, visit <u>visqueen.com</u> or contact our sales office at ± 44 (0) 333 202 6800 or <u>enquiries@visqueen.com</u>

Complete Range, Complete Solution



Visqueen Technical Support

Visqueen offer a comprehensive full nationwide technical support. Our team of CSSW qualified technical support managers provide on site design-based solutions for specifiers, contractors and builders merchants, and will ensure that from design stage to installation the project is fully risk assessed and the specification is approved by all stakeholders.

Our Technical Office, can design, prepare and manage CAD detailing, together with assisting in quantity take offs, while offering advice on technical installations and product selection.

Competency & Design

Visqueen promotes competency in building design by ensuring that its technical team possesses the necessary skills, knowledge, experience, and ethical practices. The company adopts the "golden thread of information," ensuring all project data is digitally secure and accessible throughout a building's lifecycle. This approach aligns with the Building Safety Act and aims to foster accountability and compliance with evolving regulations, providing clients with confidence in the safety and reliability of their projects.

Visqueen CPD Seminars

Visqueen's CPD Seminars offer insights into Building Regulations, Standards, and industry guidance related to damp proofing, hazardous ground gas protection, and structural waterproofing. These one-hour seminars are tailored for construction design professionals and delivered by our Technical Support Managers. Visit our website to book a free CPD.

Visqueen NF-Detailing Strip, 300mm x 10, 500mm x 10m

Visqueen Contract Design Services

Visqueen Contract Design Services offers a bespoke design service led by our team of Certified Surveyors in Structural Waterproofing (CSSW), providing experienced and specialised waterproofing design expertise for complex projects. We provide comprehensive support throughout the entire project, ensuring that all work meets the requirements of warranty providers and adheres to the highest standards of quality, reliability and current legislation.

Visqueen Training Academy

Based at our Derbyshire facility, the Visqueen Training Academy offers a variety of training programs across the UK. These include one-day product awareness sessions for distributors and builders' merchants, and intensive twoday courses for hands-on product installation training. Contact us for more information.

Technical Datasheet