

Visqueen Double Sided Vapour Control Tape, 20mm x 50m

Features and benefits

- Aggressive adhesive system - strong bond strength to timber and steel
- Visqueen's advanced adhesive technology - at low temperatures 20 x more adhesion than standard tapes
- Complete system - part of Visqueen's Vapour Check Membrane components
- Compliance - Part L Building Regulations and airtightness. Ensure nails are not used to puncture membranes.

Product description

Visqueen Vapour Control Tape is a high performance double sided tape with an 200gsm aggressive adhesive system.

The product is available in 20mm x 50m roll format containing 5 rolls per box.

Approvals and standards


- Compliant with Part L Building Regulations
- Compliant with BS 5250:2011 Code of practice for control of condensation in buildings
- Quality Management System ISO 9001:2015
- Occupational Health and Safety System ISO 18001:2007
- Environmental Management System ISO 14001:2015

Usage

The Visqueen Vapour Control Tape is used to hold the Visqueen Vapour Check vertically or horizontally against the timber stud work or metal substrate during the build process. Its other main use is to seal the Visqueen Vapour Check to the stud heads and sole plate. The tape has superior adhesion and can be used in all temperatures between -40°C to 40°C.

System components

Find your local stockist



Visqueen Double Sided Vapour Control Tape, 20mm x 50m

Storage and handling

Store in warm, dry and clean environment in its current packaging. The tape should not be exposed to long periods of ultraviolet light.

Preparation

The tape should be installed on a substrate which is free from loose friable material and free from contamination such as dust, all sharp protrusions must be removed. If required brush the surface clean prior to applying the tape.

Installation

Where the membrane is to be fixed to timber or metal frame structures, apply a continuous strip of Visqueen Double Sided Vapour Tape to all vertical and horizontal studs, head and sole plates, using a seam roller to ensure adhesion. Progressively peel of the tape release film, and apply the membrane ensuring adhesion in the tape locations.

Usable temperature range

The Visqueen Vapour Control tape has superior adhesion and can be used in all temperatures between -40°C to 40°C.

Additional information

The Visqueen Vapour Check does require permanent mechanical fixing, this will be achieved by over-boarding the Visqueen Vapour Check with a plasterboard or other construction board.

Visqueen Double Sided Vapour Control Tape, 20mm x 50m

Property	Value
Dimensions	20mm x 50m
Quantity per box	5
Application temperature range	-40°C to 40°C
Peel adhesion testing	N/25mm
Steel	53.6
PE	50.4
Wood	51.2

Health and safety information

Please refer to material safety datasheet

Visqueen Double Sided Vapour Control Tape, 20mm x 50m

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.