

VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m

Features and benefits

- Flexible - can be cut and shaped to various applications
- Multi-use - suitable for complex junctions, stanchions, patchwork and terminations
- Gas resistant aluminium core

Product description

VisqueenPro Detailing Strip is a composite of PET/aluminium and a cold weather butyl compound. It is available in roll format, 300mm x 10m and 500mm x 10m.

Approvals and standards

- Complies with the methane gas transmission rate, mass per unit area and thickness requirements of BS 8485:2015 + A1:2019 - industry standard for methane and carbon dioxide protection
- Suitable for all Characteristic Gas Situation (CS) ground gas regimes
- Conforms to the specification requirements of NHBC Amber 1 and Amber 2 applications
- Conforms to the specification requirements of BR 211:2023
- Visqueen certified with Quality Management System ISO 9001:2015
- Visqueen certified with Occupational Health and Safety System ISO 45001:2018
- Visqueen certified with Environmental Management System ISO 14001:2015


Usage

VisqueenPro Detailing Strip is used for sealing junctions and complicated detailing in Visqueen gas protection systems, waterproofing systems, and damp proofing systems. It can be used on concrete, blockwork, brickwork, particle boards, steel work, steel stanchions and wooden substrates for both vertical and horizontal application.

System components

- Visqueen HP Tanking Primer, 5L

Find your local stockist



VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m

Storage and handling

Store in a dry and clean environment in its current packaging. The product must be stored upright.

VisqueenPro Detailing Strip can be cut with a sharp retractable safety knife.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

Surfaces must be smooth and free from sharp protrusions, ensure the surface and working area is not water logged and is frost free. When applying to blockwork or brickwork the joints must be flush pointed. Prior to bonding, substrates such as masonry, concrete and steel should be primed using Visqueen HP Tanking Primer and allowed to dry thoroughly. Visqueen HP Tanking Primer must not be used on Insulation or ICF systems.

Installation

Position and peel back the VisqueenPro Detailing Strip release film and apply the pressure sensitive, self adhesive face to the prepared substrate. Apply pressure by rolling to ensure a full bond is achieved. All lap joints should be a minimum of 150mm and must be pressed and rolled to ensure damp, gas or waterproofing continuity.

When used for sealing membranes punctures, VisqueenPro Detailing Strip should be lapped at least 150mm beyond the extents of the puncture.

Usable temperature range

It is recommended that VisqueenPro Detailing Strip should be installed above -5°C. Prior to installation, ensure that frost or ice is not present on the substrate.

Additional information

The information in this datasheet was correct at the time of publication. It is the user's responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.

VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m

Property	Value
Width	300mm or 500mm
Length	10m
Application temperature range	-5°C to 40°C
Peel Adhesion BS EN 12316, Steel ASTM D1000, in N/cm @ 5°C	
- Polyethylene	20.7
- Polyethylene with no static charge	21.2
- Steel	26.9
- Concrete	28.8
Mean water vapour resistance factor, BS EN 1931, u	3960000
Mean water vapour diffusion equivalent air layer thickness BS EN 1931, (Sd) in m	4752
Mean water vapour resistance, BS EN 1931, MNs/g	23760
Mean water vapour permeability, BS EN 1931, g/m ² /day	0.03

Health and safety information

Refer to the VisqueenPro Detailing Strip safety datasheet (SDS)

VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.