

VisqueenPro Single Sided Vapour Edge Tape, 150mm x 15m

Features and benefits

- Compliance - Part L Building Regulations on airtightness
- Visqueen's advanced adhesive technology - excellent bond strength to concrete, timber plastic and steel
- Multi-use - Ideal for bridging gaps and flashing from the membrane on to challenging substrates
- Adaptable - at low temperatures 15 x more adhesion than standard tapes
- Complete system - part of Visqueen's high performance vapour membranes components

Product description

VisqueenPro Vapour Edge Tape is a composite of foil, laminated to a Valeron film, then coated with a pure acrylic adhesive system.

The product is available in roll format 150mm x 15m.

The complete airtight taping system includes:

VisqueenPro Double Sided Vapour tape 20mm x 50m

VisqueenPro Single Sided Vapour tape 75mm x 15m

VisqueenPro Vapour Edge tape - 150mm x 15m

Approvals and standards


- Compliant with Part L Building Regulations
- Compliant with BS 5250:2011 Code of practice for control of condensation in buildings
- Quality Management System ISO 9001:2015
- Occupational Health and Safety System ISO 18001:2007
- Environmental Management System ISO 14001:2015

Usage

VisqueenPro Vapour Edge Tape is used for gap bridging or flashing from the Vapour Control Membrane onto challenging substrates such as concrete, timber plastic and steel.

System components

Find your local stockist



VisqueenPro Single Sided Vapour Edge Tape, 150mm x 15m

Storage and handling

Store in warm, dry and clean environment in its current packaging. The tape should not be exposed to long periods of ultraviolet light.

Preparation

VisqueenPro Vapour Edge Tape should be installed on a substrate which is free from loose friable material and free from contamination such as dust, all sharp protrusions must be removed. If required brush the surface clean prior to applying the tape.

Installation

Apply VisqueenPro Vapour Edge Tape equidistant over the junction of the membrane and surface to which the tape will seal. Roller down the lap to ensure good adhesion.

Usable temperature range

The tape can be used in all temperatures between -5°C to 40°C.

Additional information

When over-boarding the vapour control membrane with a plasterboard or other construction board care should be taken to ensure that the membrane is not punctured, stretched or displaced during this process.

VisqueenPro Single Sided Vapour Edge Tape, 150mm x 15m

Property	Adhesion
Steel	36N/25mm*
Aluminium	35N/25mm*
Glass	35N/25mm*
PVC	35N/25mm*
PP	33N/25mm*
PMNA	36N/25mm
* Denotes cohesive failure according to AFERA 4001	
Dimensions	150mm x 15m

Health and safety information

Please refer to material safety datasheet.

VisqueenPro Single Sided Vapour Edge Tape, 150mm x 15m

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural
Waterproofing



Gas
Protection



Damp Proof
Membrane



Tapes



Damp Proof
Course



Stormwater



Vapour
Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.