

## Visqueen Ultimate Retaining Discs, 50mm long x 35mm head diameter

### Features and benefits

- Cost effective solution - Ideal for securing the pre-applied membrane in a vertical position to formwork

### Product description

A plastic fixing disc 35mm head and 50mm long. Supplied 500 per box.

### Approvals and standards


- Third party accreditation - BDA approved system component
- Suitable for use as a Type A Barrier Membrane (Tanking Membrane) to BS 8102:2009
- Quality Management System ISO 9001:2015

### Usage

The Visqueen Ultimate Retaining Discs secures Visqueen Pre Applied Membrane or Visqueen Ultimate GeoSeal to vertical applications such as formwork or adjoining.

### System components

### Find your local stockist



## Visqueen Ultimate Retaining Discs, 50mm long x 35mm head diameter

### Storage and handling

Store in warm, dry and clean environment in its current packaging.

### Preparation

The formwork surfaces must be smooth and free from sharp protrusions, ensure the surface and working area is not water logged.

### Installation

When installed vertically, the membrane should be pre-applied to temporary formwork or the adjoining structure. Visqueen Retaining Discs are available to provide a means for securing the leading edge of the membrane to the temporary formwork. The barrier should be installed with the smooth black surface facing the formwork. Using oval nails, Visqueen Retaining Discs should be mechanically fixed at maximum 400mm centres to the internal face of the shuttering. Using a suitable power tool and 6mm drill bit to create a pilot hole in the barrier, it should be secured over the protruding section of the retaining disc. The top edge of the barrier should be trimmed to approximately 10mm below the top edge of the slab. Once the concrete has set, the oval nails should be removed by pulling through from the external face of the shuttering. When the temporary formwork is removed the Visqueen Retaining Discs should be visible on the external (smooth black) face of the barrier. Continuity of the barrier system with the damp or gas proof course is maintained using Visqueen Gas Resistant Self Adhesive Membrane.

### Usable temperature range

It is recommended that Visqueen Ultimate Retaining disc should be used above 5°C.

### Additional information

Care must be taken to ensure the outer box remains dry.

### Health and safety information

Please refer to material safety datasheet.

## Visqueen Ultimate Retaining Discs, 50mm long x 35mm head diameter

### About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website ([www.visqueen.com](http://www.visqueen.com)) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or [enquiries@visqueen.com](mailto:enquiries@visqueen.com)

### Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

### Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

### Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

### Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

### Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.