

## Visqueen Zedex Jointing Tape, 100mm x 15m

### Features and benefits

- Excellent adhesion - ensures secure lap joints
- Barrier - provides excellent resistance to water ingress and gases
- Extra wide - ensures DPC joint compliance and good bond strength in demanding conditions

### Product description

Visqueen Zedex Jointing Tape is a double sided butyl based compound with an oversize quick release film. It is available in roll format 100mm x 15m and coloured black.

### Approvals and standards


- Third party certification - BBA Certificated as system component
- Quality Management System ISO 9001

### Usage

Visqueen Zedex Jointing Tape is used to bond Visqueen damp proof courses (DPC): Zedex, Polythene and Visqueen Gas Resistant DPCs. It can also be used internally and externally and is suitable in compressed load applications such as masonry walls.

### System components

### Find your local stockist



## Visqueen Zedex Jointing Tape, 100mm x 15m

### Storage and handling

Store horizontally in warm, dry and clean environment in its current packaging. The tape should not be exposed to long periods of ultraviolet light. In very cold weather, prior to use ensure that the material is stored in warm conditions above 5°C.

### Preparation

Ensure all surfaces are clean and dry, if applying to a surface that is not a membrane i.e. concrete, ensure that the surface is free from loose friable material prior to using the Visqueen HP Tanking Primer. The membrane joint surfaces should be dry and free from contamination such as dust or sand. The tape can be cut with a sharp knife.

### Installation

Apply tape to the lap area of the laid sheet starting approximately 50mm from the membrane edge and remove quick release paper. Overlap adjoining membrane by minimum 100mm and apply pressure to the jointed area to ensure a watertight seal has been achieved. When used in gas protection applications the lap joints should then be sealed using the appropriate Visqueen Gas Resistant Lap tape. Once the tape is applied, the completed lap should be well rolled with firm pressured to ensure complete adhesion and continuity.

### Usable temperature range

It is recommended that Visqueen Zedex Jointing Tape and other system components should be used above 5°C.

### Additional information

The product must not be used in non combustible applications.

## Visqueen Zedex Jointing Tape, 100mm x 15m

Property	Result
Width	100mm
Length	15m
Colour	Black
Adhesive type	Butyl
Dynamic Shear Adhesion	18 N/cm2
Dynamic Tensile Adhesion	18 N/cm2
180° Peel Adhesion	11 N/cm2
Service Temperature Range	-40 to 90oC
Application temperature	>5oC

### Health and safety information

Please refer to material safety datasheet.

## Visqueen Zedex Jointing Tape, 100mm x 15m

### About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website ([www.visqueen.com](http://www.visqueen.com)) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or [enquiries@visqueen.com](mailto:enquiries@visqueen.com)

### Complete Range, Complete Solution



Structural  
Waterproofing



Gas  
Protection



Damp Proof  
Membrane



Tapes



Damp Proof  
Course



Stormwater



Vapour  
Control

### Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

### Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

### Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

### Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.