

Visqueen Clear Temporary Protective Sheeting (TPS)

Features and benefits

- Provides high visual clarity
- Large roll format - Ideal for draping, screening, covering or hanging
- Provides protection against showers and dust
- Provides protection for light duty applications whilst buildings undergo refurbishment or in new build projects

Product description

Visqueen Clear Temporary Protective Sheeting (TPS) is a clear polyethylene temporary protective sheeting which provides high visual clarity. It is supplied on a core in rolls of 4m x 25m.

Approvals and standards

- Visqueen certified with Quality Management System ISO 9001:2015
- Visqueen certified with Occupational Health and Safety System ISO 45001:2018
- Visqueen certified with Environmental Management System ISO 14001:2015


Usage

Visqueen Clear Temporary Protective Sheeting (TPS) is a polyethylene sheet suitable for screening, wrapping large objects and other site construction materials such as bricks, blocks, timber and plasterboards. It's ideal for when the protected product(s) needs to remain visible from beneath the sheeting. It can be used in various other applications whilst buildings undergo refurbishment work, or in new build construction projects whilst also providing protection from showers and dust.

System components

- VisqueenPro Single Sided Tape, 75mm x 25m

Find your local stockist



Visqueen Clear Temporary Protective Sheeting (TPS)

Storage and handling

Visqueen Clear Temporary Protective Sheeting (TPS) should be stored horizontally, under cover in its original packaging.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

Visqueen Clear Temporary Protective Sheeting (TPS) can be cut with a sharp retractable safety knife or robust scissors.

Surfaces to be covered should be free from sharp protrusions. The film should be installed as soon as all surfaces or fixtures are clean.

Installation

Unroll Visqueen Clear Temporary Protective Sheeting (TPS) and cut to fit the area that needs protecting.

For large covered areas it may be necessary to lap adjacent film sheets and a taped joint is recommended to ensure continuity of protection. When taping, allow an overlap of at least 50mm and secure the joint using VisqueenPro Single Sided Tape. Prior to taping ensure that the lap area is clean and free from dust and any moisture.

Usable temperature range

It is recommended that VisqueenPro Single Sided Tape should not be installed below 5°C. There are no temperature restrictions for installation of Visqueen Clear Temporary Protective Sheeting (TPS).

Additional information

The information in this datasheet was correct at the time of publication. It is the user's responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.



Visqueen Clear Temporary Protective Sheeting (TPS)

Property	Value
Roll size	4m x 25m
VisqueenPro Single Sided Tape - roll size	75mm x 25m

Health and safety information

Refer to Visqueen Clear Temporary Protective Sheeting (TPS) safety datasheet (SDS).

Visqueen Clear Temporary Protective Sheeting (TPS)

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.