



Visqueen Gas Vent Mat

Features and benefits

- Large format rolls - rapid installation
- Cost effective - less contaminated soil to be removed compared to pipe and gravel systems
- Complies with BS8485:2015 + A1:2019 - system achieves between 0.5 and 1.5 points
- Full range of system components - provides various methods of exhausting gases to atmosphere

Product description

Visqueen Gas Vent Mat is a geocomposite void former comprising a cusped high density polyethylene (HDPE) core bonded to a nonwoven polypropylene geotextile filter membrane. Visqueen Gas Vent Mat is 25mm thick and supplied in rolls 900mm x 50m.

Approvals and standards

- Quality Management System ISO 9001:2015

Usage


Visqueen Gas Vent Mat is designed to create a 25mm deep void beneath reinforced concrete ground floor slabs. Hazardous ground gases or volatile organic compounds (VOCs) are collected within the void and dispersed to atmosphere via a designed arrangement of Visqueen connectors and venting components, collectively managing and effectively diluting the collected gases.

Where high gas concentrations have been recorded the vent mat can be laid in a blanket format with the individual mats being butted together. Where the gas concentrations are low or where pressure relief is required the vent mat can be laid in a strip format with the mat being laid at predetermined spacings.

System components

- Visqueen Venting Pipework and Connectors
- VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m

Find your local stockist





Visqueen Gas Vent Mat

Storage and handling

Visqueen Gas Vent Mat should be stored on end, under cover in the original packaging.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

Visqueen Gas Vent Mat should be installed on a compacted layer, free from voids or protrusions.

To prevent wind uplift when working on exposed sites, it is advisable to consider loading the vent mat with sandbags or other ballast as installation progresses.

The vent mat can be cut with a sharp retractable safety knife.

Installation

Unroll Visqueen Gas Vent Mat in position. Turn over so that the geotextile filter membrane layer faces downwards i.e. towards the substrate.

When laid in a blanket format, all joints should be butted with the overlap strip of geotextile filter membrane extending beneath the adjacent vent mat.

When laid in strip format, end laps should be butted with the overlap strip of geotextile filter membrane, when present, extending beneath the adjacent vent mat.

Where necessary the vent mat can be cut around columns, pipes and other such penetrations.

For effective gas dispersal, the vent mat should be connected to a means of exhausting the collected gases to atmosphere e.g. Visqueen Adjustable Z Vents and Airbricks, Visqueen Pro Gas Vent Boxes or Visqueen Gas Vent Bollards.

Usable temperature range

There are no temperature range restrictions for installing Visqueen Gas Vent Mat and associated system components.

Additional information

When designing the venting or pressure relief system careful consideration should be given to the substructure elements such as positioning of foundation pads and ground beams so as to avoid over complex detailing

For assistance with gas venting or gas pressure relief design and detailing, contact Visqueen Technical Services +44 (0) 333 202 6800



Visqueen Gas Vent Mat

Property	Test method	Units	Value
Width		mm	900
Length		m	50
Thickness	EN ISO 9863-1	mm	25
Compressive strength	EN ISO 25619-2	kN/m ²	300
Roll weight		kg	74
Roll diameter		m	1.3
In-plane air flow capacity with soft/hard platens @ 20mm and 100kPa	BE EN ISO 12958	l/m/s	155
Shear Strength	BE EN ISO 13426-2	kN	1

Health and safety information

Refer to the Visqueen Gas Vent Mat material safety datasheet (MSDS).

Visqueen Gas Vent Mat

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.

