

Visqueen High Performance Vapour Barrier

Features and benefits

- Versatile application - used within floor, wall and roof constructions
- Suitable for BS 5250: 2011 class 4 and 5 conditions - prevents damage to structure and insulation
- Single wound roll - rapid installation

Product description

Visqueen High Performance Vapour Barrier is a multi-layer reinforced polyethylene barrier with a 20 micron aluminium foil. The barrier is coloured blue on the upper surface and silver on the reverse. The product is supplied in single wound rolls (not folded), 2m x 50m long.

Approvals and standards

- Compliant with Part L Building Regulations
- Compliant with BS 5250:2011 Code of practice for control of condensation in buildings
- CE Mark EN 13984:2013
- Quality Management System ISO 9001:2015
- Occupational Health and Safety System ISO 18001:2007
- Environmental Management System ISO 14001:2015

Usage


Visqueen High Performance Vapour Barrier is used in high condensation risk buildings to remove the risk of interstitial condensation within the structure as well as improving the air-tightness of the building.

The barrier is designed to be installed to the warm side of floors, walls and roofs subjected to humidity levels more than 60% at 20°C (BS 5250: 2011 class 4 and 5 condition) e.g. domestic dwellings with high occupancy, sports halls, swimming pools, communal shower areas, laundries, canteens and buildings with wet industrial processes.

System components

- Visqueen ProDouble Sided Vapour Control Tape, 20mm x 50m
- VisqueenPro Single Sided Vapour Tape, 75mm x 15m
- Visqueen ProVapour Edge Tape, 150mm x 15m

Find your local stockist



Visqueen High Performance Vapour Barrier

Storage and handling

Visqueen High Performance Vapour Barrier should be stored horizontally, under cover in its original packaging.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

Ensure surfaces are smooth, clean and dust free. When bonding the barrier to the substrate, e.g. timber or metal studs, the surface should be dry.

Installation

Visqueen High Performance Vapour Barrier should be installed in accordance with the recommendations of BS 5250:2002 Code of practice for control of condensation in buildings. The barrier should be installed on the warm side of the insulated structure, with care being taken to ensure that all laps, penetrations and abutments are sealed. The membrane should be continuous in order to ensure optimum vapour control performance.

Where the barrier is to be fixed to timber or metal frame structures, apply a continuous strip of Visqueen Pro Double Sided Vapour Tape to all vertical and horizontal studs, head and sole plates, using a seam roller to ensure adhesion. Progressively peel off the tape release film, and apply the barrier ensuring adhesion in the tape locations.

The barrier should be installed with the foil (silver) side facing the warm inside of the building.

All joints in the barrier should be lapped by a minimum of 75mm and sealed with Visqueen Pro Single Sided Vapour Tape applied centrally over the lap. To aid formation laps should be made over a solid substrate.

Ensure barrier continuity at the junction of horizontal and vertical substrates. Seal abutments with Visqueen Pro Vapour Edge Tape applied centrally over the junction. Failure to suitably connect the barrier to other building elements will severely reduce vapour control performance.

Ensure the barrier is not damaged in service due to residual heat from light fittings. The barrier should not be subjected to gravity forces (unsupported) such as on the underside of roof decks or the underside of floor structures, and should be suitably mechanically secured to ensure that it remains in position during service.

Usable temperature range

It is recommended that Visqueen High Performance Vapour Barrier and all associated system components should not be used below 0°C.

Additional information

For additional detailing information, contact Visqueen Technical Services +44 (0) 333 202 6800

Visqueen High Performance Vapour Barrier

Property	Test method	Units	Compliance criteria	Result
Visible defects	EN 1850 -2	-	Pass/Fail	Pass
Length	EN 1848-2	m	-0%/+10%	50
Width	EN 1848-2	m	-0%/+10%	2
Thickness	EN 1849-2	mm	-12.5%/+12.5%	0.52
Mass	EN 1849-2	g/m ²	-12.5%/+12.5%	345
Tensile strength - MD	EN 12311	N	MLV	515
Tensile strength - CD	EN 12311	N	MLV	550
Tensile elongation - MD	EN 12311	%	MLV	17
Tensile elongation - CD	EN 12311	%	MLV	15
Joint strength	EN 12317-2	N	MLV	332
Watertightness 2kPa	EN 1928	-	Pass/Fail	Pass
Resistance to impact	EN 12691	mm	>MLV	200
Low temperature flexibility	EN 495-5	°C	-40	Pass
Durability (artificial ageing)	EN 1296 and EN 1928	-	Pass/Fail	Pass
Durability chemical resistance	EN 1847	-	Pass/Fail	Pass
Resistance to tearing (nail shank) CD	EN 12310-1	N	MDV	358
Resistance to tearing (nail shank) MD	EN 12310-1	N	MDV	368
Resistance to static loading	EN 12730	kg	MLV	20
Water vapour transmission - resistance	EN 1931	MNs/g	MDV	7000
Mean moisture resistance factor (μ)				426 x 10 ³
Water vapour transmission - permeability	EN 1931	g/m ² /d	MDV	0.03
Reaction to fire	EN 13501-1	Class	MDV	F

Health and safety information

Refer to the Visqueen High Performance Vapour Barrier material safety datasheet (MSDS).

Visqueen High Performance Vapour Barrier

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.

